

## Bioprocess Tubing

Cleanroom Manufactured

NEW

KFlex

### KFlex

RoHS Compliant

Low Extractables Biomedical Tubing

Biomedical • Pharmaceutical • Bioprocess



Flexible Tubing Product With a Kynar Flowpath

- Low extractables / leachables liner component
- Kynar liner meets USP Class VI requirements
- More flexible than tubing extruded from 100% Kynar
- Animal derivative free Kynar® liner

Tube Number	ID		OD Nominal		Wall	Standard Roll
KFLEX .5-1.5	1/32"	.0312"	3/32"	.093"	1/32"	50 ft.
KFLEX 1-2	1/16"	.0625"	1/8"	.125"	1/32"	50 ft.
KFLEX 1.5-2.5	3/32"	.0937"	5/32"	.156"	1/32"	50 ft.
KFLEX 2-3	1/8"	.125"	3/16"	.187"	1/32"	50 ft.
KFLEX 2-4	1/8"	.125"	1/4"	.250"	1/16"	50 ft.
KFLEX 170-4	11/64"	.170"	1/4"	.250"	13/32"	50 ft.
KFLEX 3-4	3/16"	.187"	1/4"	.250"	1/32"	50 ft.
KFLEX 3-5	3/16"	.187"	5/16"	.312"	1/16"	50 ft.
KFLEX 4-6	1/4"	.265"	3/8"	.390"	1/16"	50 ft.
KFLEX 5-7	5/16"	.323"	7/16"	.448"	1/16"	50 ft.
KFLEX 6-8	3/8"	.385"	1/2"	.510"	1/16"	50 ft.
KFLEX 8-10	1/2"	.510"	5/8"	.635"	1/16"	50 ft.
KFLEX 8-12	1/2"	.510"	3/4"	.760"	1/8"	50 ft.
KFLEX 10-14	5/8"	.635"	7/8"	.885"	1/8"	50 ft.
KFLEX 12-16	3/4"	.760"	1"	1.010"	1/8"	50 ft.

- Low gas and oxygen permeability
- No DEHP additives
- Chemical resistant Kynar liner
- Sterilize using E-beam

High Temp. Range: 80 °C (176 °F) • Shore A 85 hardness

Cleanroom Manufactured

ISO 9001  
Quality System

millimeter sizes available on request