



Vertically Integrated, Made in the USA




THE SPECIALTY MFG. CO.

5858 Centerville Road • St. Paul, MN 55127-6804

Tel: (651) 653-0599 • Fax: (651) 653-0989

www.specialtymfg.com • e-mail: info@specialtymfg.com

426 SERIES CHECK VALVE



Design Considerations

The 426 Series Check Valve design promotes multiple configurations to fit the exact end use application. Gray PVC with 1 psi stainless spring and ball is the standard configuration. Most PVC and White Filled Polypropylene configurations are available as NSF Standard 42 Certified. Nylon, PVDF (Kynar®) and Glass Filled Polypropylene are available for chemical resistance applications. MakroBlend is an NSF Standard 51 Certified Material. Hastelloy is a superior chemically resistant spring material. Teflon® balls are standard with Hastelloy springs for chemical resistance applications.

- Maximum Operating Pressure — 125 psi
- Maximum Operating Temperature — 140°F
- Seat Area Open Diameter — .250

Options

Material Options	Gray PVC (Standard), White PVC, Black Polypropylene, White Polypropylene, Black Nylon, White Nylon, MakroBlend, Black PVDF (Kynar®)	
Seal Options	Buna-N, Ethylene Propylene, Fluoroelastomer (Viton®)	
End Options	1/8, 1/4 Male and Female NPT 1/8, 1/4, 5/16, 3/8, 1/2 Hose Barb 1/8, 1/4 JACO (Not NSF 42 Certified)	1/4, 3/8 SMC Push-To-Connect 3/8 BIB (Smooth Barb)
Cracking Pressure	302 Stainless Spring - 1/3 psi, 1 psi (Standard), 1.5, 3, 5, 7, 10, 12 psi or No Spring, Hastelloy Spring - 1/3, 1, 3, 5, 12 psi	
Ball Material	316 Stainless - Standard With Stainless Spring Teflon® - Standard With Hastelloy Spring	

Example of How To Order

Body Material PVC	Inlet End 1/4 MNPT	Outlet End 1/4 FNPT	Seal Buna-N	Spring 3 psi	Ball Material Stainless
-----------------------------	------------------------------	-------------------------------	-----------------------	------------------------	-----------------------------------

SMC Part Number: PVC 426-4M4F-B,3#

The flow arrow on the body will point from Inlet to Outlet. SMC Part Numbers are a description of the valve as read left to right, Inlet to Outlet.

Example: PVC 426-4M4F-B,3# = 1/4 MNPT Inlet x 1/4 FNPT Outlet

SMC will quote alternate materials or customize our standard products when quantities ensure competitive pricing.